



Contiguous Allocation

- Contiguous allocation
 - allocate contiguous memory space for each user program
- MMU: address translation and protection
 - Assume that logical address always starts from 0;
 - Relocation register contains starting physical address;
 - Limit register contains range of logical addresses each logical address must be less than the limit register.



Contiguous Allocation (Cont.)

- Memory space allocation
 - Available memory blocks of various size are scattered throughout memory.
 - When a process arrives, it is allocated memory from a free block large enough to accommodate it.
 - Operating system maintains information about:
 a) allocated partitions
 b) free partitions (hole)





Space Allocation Strategies

How to satisfy a request of size *n* from a list of free memory blocks (holes).

- First-fit: Allocate the *first* hole that is big enough.
- Best-fit: Allocate the *smallest* hole that is big enough; must search entire list, unless ordered by size. Produces the smallest leftover hole.
- Worst-fit: Allocate the *largest* hole; max-heap (the data structure) can help here.

Compare them on speed & space utilization.






CPU

Pd

page table



physical


address


f d


10000 . . . 0000


physical

memory









Disclaimer

.

 Parts of the lecture slides contain original work of Abraham Silberschatz, Peter B. Galvin, Greg Gagne, Andrew S. Tanenbaum, and Gary Nutt. The slides are intended for the sole purpose of instruction of operating systems at the University of Rochester. All copyrighted materials belong to their original owner(s).

CSC 256/456 - Spring 2007

17