

Natural Logic (NLog) & EL/EPILOG

NLog: Enables some obvious lexical inferences to be made easily from parsed, annotated NL

Two main ideas:

1. Replace terms by more general ones in positive (upward entailing) phrasal contexts, and by more specific ones in negative (downward entailing) ones. So, inference is "polarity-based".

e.g., All dogs bark → All poodles make noises

e.g., When it rains, the basement gets flooded
→ When it pours, something gets wet

e.g., The Moon is made of rock, not cheese
The Moon is made of minerals, not Cabral's blue cheese

2. Infer the (positive or negated) complement of implicative & presuppositional verbs

e.g., Ed managed to graduate → Ed graduated

e.g., Ed failed to graduate → Ed did not graduate

e.g., Ed knows he is lazy → Ed is lazy

Combining these methods

e.g., Ed managed to buy a truck
+ implic. ↓ +ve ↓ +ve
→ Ed acquired a vehicle

e.g., (from MacCartney & Manning, 2009)

Jimmy Dean refused to move without his blue jeans
+ve -ve -ve entail. -ve & -ve = +ve
James Dean did not dance without pants

Episodic Logic (EL) & the EPILOG inference engine

EL is an extension of FOL to cover modification and reification of predicates & sentences, and to allow association of episodes with arbitrary sentences.

e.g., Ed knows that he is very lazy → (approximately)

($\exists e: [e \text{ at-about Now}34]$) WordNet-based disambiguation

Skelemize

$[[\text{Ed knows}_3.v (\text{that } [\text{Ed (very lazy)}])] \star\star e]$

Axiom: $(\forall x (\forall e (\# p : [[x \text{ knows}_3.p] \star\star e]) \text{ "characterizes" } [[x \text{ believes}_1.p] \star\star e] \& [p \text{ True}]))$

$[[\text{Ed knows}_3.y (\text{that } [\text{Ed (very lazy)}])] \star\star E3]$

$[[\text{Ed believes}_1.v (\text{that } [\text{Ed (very lazy)}])] \star\star E3]$

(partially) describes

EL also allows schemas (containing syntactic metavariables)

$$(\forall_{\text{wff}} w [[(\text{that } w) \text{ True}] \Leftrightarrow w])$$

substitute any wff for w

$$(\forall_{\text{pred }} P (\forall_{\text{term }} t [[t \text{ (very } P)] \Rightarrow [t P]]))$$

Thus, being very lazy implies being lazy

So we can derive

[Ed lazy] ("lazy" construed as an enduring, nonepisodic property)

In general, EL (implemented in the EPILOG engine)
uses

- generalized polarity-based "forward & backward inference" (cf. resolution, w/o conversion to clauses)

$$\text{forward: } \frac{\text{MAJ}^-(\varphi), \text{MIN}^+(\varphi')}{\text{MAJ}_\sigma^-(\neg(\text{MIN}_\sigma^+(\perp)))} \quad \sigma \text{ unifies } (\varphi, \varphi')$$

$$\text{falsity } (\equiv \square)$$

$$\text{e.g., } \neg(\text{Dog}(x)) \vee \text{Pet}(x), \quad (\text{Dog}(Fifi)) \vee \text{Cat}(Fifi) \quad \sigma = (x/Fifi)$$

$$\begin{aligned} \text{actually, } & \neg(\neg(\perp \vee \text{Cat}(Fifi))) \vee \text{Pet}(Fifi) \\ (\text{Nr: } [\exists x \text{ dog}] [\exists x \text{ pet}]) & = \text{Cat}(Fifi) \vee \text{Pet}(Fifi) \text{ as for resolution} \end{aligned}$$

- Some natural deduction rules :

- assumption of antecedent in proving $[\varphi \Rightarrow \psi]$
- assumption of false disjunct in proving $[\varphi \vee \psi]$
- some others

- Specialists (e.g., for taxonomies, parts, times, arithmetic, ...) to accelerate inference.